


CONTRACTORS ACRYLIC PAINT



PRODUCT INFORMATION

- Designed for interior use.
- Excellent obliterating properties.
- Good flow and leveling properties.
- Dries quickly enabling the application of 2 topcoats in one day.
- Is easy to apply, use a brush, roller or spray.
- Has good UV and weather resistance.
- **LOW VOC LEVEL [10g/L]**
- Non hazardous, non toxic, and both environmentally and user friendly.



PRODUCT CODE AC007

PRODUCT DATA INFORMATION SHEET

PRODUCT DESCRIPTION

Marmoran Marmocote M75 is a good quality contractor's paint and is suitable for application to a variety of building surfaces including new cement plaster, concrete, gypsum plaster and a wide variety of composition boards. Marmoran Marmocote M75 has a matt finish that is moderately durable. A particular advantage of Marmoran Marmocote M75 is its excellent obliterating properties.

COLOUR & PACKAGING

- Available in White.
- Packed in 5 and 20 L containers.

GENERAL CONSIDERATION REGARDING APPLICATION

CLIMATIC CONDITIONS

Adequate protection should be provided against rain and sub-zero temperatures for a period of not less than 24 hours after application. The coating should never be applied during adverse weather conditions, or on wet surfaces. Even if the weather seems fit for painting, there may be condensation if the temperature of the substrate is at or below the dew point (temperature at which the atmospheric humidity condenses e.g. as dew) the product should only be applied when the temperature of the substrate is at least 2 deg C above dew point. In hot climates, the coating should be applied during the morning and late afternoon hours and if possible away from direct sunlight. Variations in temperatures will affect drying times.

APPLICATION

- Please refer to our notes on **BEST PRACTICES FOR SURFACE PREPARATION**.
- **Inspect the substrate** The plaster should be a fine wood float finish and adequate time should be allowed for it to cure prior to the application of any specialised, semi-specialised coating or paint.
- **Prepare the substrate** appropriately to ensure that the surface is clean, dry and sound.
- Ensure that the **scaffold** be positioned at a comfortable distance away from the surface so that application technique is not compromised. (400-600mm).
- **Expansion/control joints** should be sealed before painting and should be finished with a compound which will accept water based finishing products. A suitable Marmoran Primer may then be applied directly over these joints.
- **Check** spread rates & tools. May be applied by brush, roller or spray.
- The product is supplied ready for use. **DO NOT THIN**. Mix gently with a flat paddle before and during application. Clean with water.

SPECIFICATION for MARMORAN MARMOCOTE M75

NEW WORK

Inspect prepare the substrate appropriately to ensure that the surface is clean, dry and sound.

Apply 2-3 coats of Marmoran MARMOCOTE M75 SABS 1586 GRADE 4 to achieve complete obliteration.

Allow for drying time between coats.

Wet Film 167- 125µ per coat **Dry Film** 47- 35µ per coat

REDECORATION

Prepare the surface by removing all loose and flaking paint, dirt, grease and grime. Make good all cracks and defects and then repair and prime to match the existing surface. Proceed as for new work.

PRODUCT DATA

Composition Acrylic Copolymer Resin Additives, Pigments, Extenders.

Solvent Type Water

Solids **Volume** 28% ± 2% **Mass** 49% ± 2%

VOC LEVEL 10g/L [0.71%]
The GREEN SEAL STANDARD is 50g/L [3.8%] for flat coatings.

Drying Times **Surface Dry:** 1 hour **Hard Dry:** 12 hours **Over coating Time:** 12 hours
@ 25 deg C, Higher temperatures will accelerate the drying times (± halved for every 10 °C increase)
65% RH Lower temperatures will retard the drying times (± doubled for every 10 °C decrease)

Theoretical 6-8 m² L / coat

Spread rate This figure is indicative, and subject to applicator skill and substrate type and condition.
Actual spread rates must be determined by the Applicator.

Shelf life & 6 - 8 Months in unopened containers.

Storage Store in a cool dry and well ventilated place away from excessive heat or an open flame.
Do not allow to freeze.

Transport Non hazardous in accordance with Transportation and Classification of Dangerous Goods Act (1996)

Handling & Safety This product is water based and non-toxic. Keep out of reach of children. It does contain chemicals that may be irritants to mammalian tissue. Appropriate protective clothing must be worn. Protect eyes and skin from exposure. If the product is being sprayed, ensure adequate ventilation and ensure the use of proper ventilated masks. Wash spillages immediately with water. Do not induce vomiting if swallowed. Consult a physician if irritation of skin persists or if product is ingested. Gather up environmental spillages, and dispose of in accordance with regulations of the local authorities.

Disclaimer All information contained herein is given in good faith, based on our specialised knowledge and experience. We reserve the right to effect changes to product and specification alike in the interest of product development and improving technology.