



Sparkle sparkle sparkle!

A CLEAR PROTECTIVE AQUEOUS GLAZE COAT

THAT ADDS A NEW DIMENSION TO THE FINAL COAT



#### PRODUCT DESCRIPTION

Glitter glaze is a superior quality clear coating based on a high performance proprietary Acrylic Resin of outstanding quality. Glitter glaze may be used to overcoat many of the Marmoran Coating Systems to provide enhanced protective properties.

#### FEATURES & BENEFITS

- enhanced protective properties
- excellent impact and abrasion resistance
- controlled Water Vapour Permeability enabling the substrate to "Breathe"
- non-hazardous, non-toxic and both environmentally and user friendly
- superior wash ability and detergent resistance and resistance to dirt pickup
- **ECO FRIENDLY - VOC LEVEL 0g/L 0.00%**

All Marmoran Products are tested to National and International Standards by independent laboratories.

#### USES

Designed for interior and exterior (under cover) use as a protective coating over a wide range of Marmoran Coating Systems.

#### COLOUR & PACKAGING

Glitter glaze is packed in 5 and 20 L containers.

**PRODUCT CODE**

**AS022B**

**PRODUCT DATA INFORMATION SHEET**

**GENERAL CONSIDERATION REGARDING APPLICATION APPLICATION**

- The product is supplied ready for use – do not thin.
- It is extremely important that the product is mixed gently with a flat paddle before and during application to ensure the even distribution of the glitter particles.
- Applied by brush, lambs-wool, short nap mohair roller.
- Once the specified Marmoran Wall Coating has fully cured apply 2 coats of Marmoran Glitter Glaze.
- Spread rate: 6-8 m<sup>2</sup>/L/ coat. Cross hatch to ensure even coverage. Allow to cure between coats.
- **WFT:** 167-125µ per coat    **DFT:** 28-21µ per coat

<b>PRODUCT DATA</b>	
Composition	Adhesion promoted Pure Acrylic Resin.
Solvent Type	Water
Solids	Volume 17% ± 2%    Mass 18% ± 2%
VOC LEVEL	<b>0g/L 0.00%</b>
Drying Times @ 25° C 65% RH	Surface dry: 2 hours    Hard Dry: 6-12 hours    Over coating time: 12-24 hours. Higher temperatures will accelerate the drying times (± halved for every 10 ° C increase) Lower temperatures will retard the drying times (±doubled for every 10 °C decrease)
Typical Spread Rate	6-8 m <sup>2</sup> / L / coat. Apply 1 or 2 coats, crosshatch to ensure even coverage. This figure is indicative, and subject to applicator skill and substrate type and condition. Actual spread rates must therefore be determined by the Applicator.
Shelf Life and Storage	6 - 8 Months in unopened containers. Store in a cool dry and well ventilated place away from excessive heat or open flame. Do not allow to freeze.
<b>TRANSPORT</b>	This product is non-hazardous in accordance with Transportation and Classification of Dangerous Goods Act (1996)
<b>HANDLING &amp; SAFETY</b>	This product is water based and non-toxic. Keep out of reach of children. It does contain chemicals that may be irritants to mammalian tissue. Appropriate protective clothing must be worn. Protect eyes and skin from exposure. If the product is being sprayed, ensure adequate ventilation and ensure the use of proper ventilated masks. Wash spillages immediately with water. Do not induce vomiting if swallowed. Consult a physician if irritation of skin persists or if product is ingested. Gather up environmental spillages, and dispose of in accordance with regulations of the local authorities.
<b>DISCLAIMER</b>	All information contained herein is given in good faith, based on our specialised knowledge and experience. We reserve the right to effect changes to product and specification alike in the interest of product development and improving technology.